## **P/N TEI15.1-1U**







Display Features Overview			
Backlight	High bright LED sunlight readable (optional)		
Finish	Black powder coat standard		
Mount	19 inch rack mount		
User Controls	Front mounted sealed silicone		
RoHS	Lead free RoHS compliant (optional)		
Cooling	Natural Convection / Fan		

Display Characteristics				
Display size	15.0" diagonal			
Resolution	1024 x 768 colored pixels			
Colors	16.7 million			
Pixel Pitch	0.297mm(V) x 0.297mm(H)			
Brightness	300 cd/m^2			
Viewing Angle	+/- 70 deg horizontal : +/- 70 deg vertical			
Contrast Ratio	800:1			
Power	External 100-240 VAC universal			
Signal Connector	D-sub 15 pin & DVI			
Input Signal	RGB standard analog			
User Control	OSD (auto Saving)			
Plug and Play	VES DDC1/2B			
Power Management	VESA DPMS compliant			
Data Inputs				
USB	(X3) usb 2.0 standard (+ 1 internal for touch screen)			
ETHERNET	(X1) 10/100 Base T			
RS232	(x1) RS232 (over Ethernet RJ45 style line)			
Computer Specifications				
CPU	600 Mhz processor (standard)	Hard Disk	8GB solid state drive	
Memory	256 MB, DDR	LAN	10/100 Base T	
Operating System	WIN-XP, QNX, Linux	Mouse	Key board with track ball	
Computer Options				
CPU	400 MHz up to 2.5 Ghz Intel Core i7	Memory	Up to 4 GB DDR2 SODIMM with Intel Core i7	
CPU (low power)	Intel Atom 1.1-1.6 Ghz (2.64 watts TDP with 45nm process)	Hard Disk	Up to 512GB solid state	
X-term	Thinmanager capable			
Environmental Characteristics				
Operating temp	-10 to 50 C	Non-operating	-40 to 60C	
Mechanical Characteristics				
Rack mount	1U 19 inch rack mount design	Weight	Less than 30 lbs	
Display Options				
Touch Screen	Resistive, Capacitive, acoustic. RS232 or USB connection	High Bright	Up to 1000 nits	
Video input	NTSC PAL	DC power	8-16VDC & 18-36 VDC	